

SAFETY DATA SHEET CALCIMENT® LKD

SECTION 1. IDENTIFICATION		
Product Name	Calciment® LKD	
Synonyms	Kiln Dust, Lime Kiln Dust, LKD, Envirolime	
Recommended Uses	pH adjustment; soil conditioning; soil stabilization; solidification; and dewatering.	
Distributor	Mintek Resources 3725 Pentagon Blvd. Suite 100 Beavercreek, OH 45431 Phone: 937-431-0218	
Emergency Contact	VelocityEHS: (800) 255-3924 (MIS8507735)	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification	Physical Hazards None		
	Health Hazards		0
	Skin Irritation Eye Damage		Category 2
	Carcinogenicity		Category 1 Category 1A
	Specific Target Organ To	vicity – Single Exposure	Category 3
		xicity – Repeated Exposure	Category 1
GHS Label Elements	Signal Word	Danger	
	Hazard Statements	Causes skin irritation.	
		Causes serious eye damage.	
		May cause respiratory irritation.	
		May cause cancer through inhala	tion.
		Causes damage to lungs through repeated exposure by inhalation. May react violently with water, re	leasing heat which
		can ignite combustible materials	
	Precautionary	Obtain special instructions before	
	Statements	Do not handle until all safety pred	cautions have been
		read and understood.	
		Keep container tightly closed.	
		Do not breathe dust.	
		Wash thoroughly after handling.	
		Do not eat, drink, or smoke when	using this product.
		Use only outdoors or in well-vent	ilated area.
		Wear protective gloves, clothing,	and eye protection.
		Do not use water on material spil	lls.
	Pictograms		



SECTION 3. COMPOSITION

Chemical name	% by weight	CAS#
Calcium Carbonate	0-90	13117-65-3
Calcium Oxide	0-50	1305-788
Calcium Hydroxide	0-70	1305-62-0
Calcium Magnesium Carbonate	0-50	16389-88-1
Calcium Magnesium Oxide	0-50	37247-91-9
Magnesium Carbonate	0-5	546-93-0
Magnesium Oxide	0-5	1309-48-4
Silica-Crystalline Quartz	< 10	14808-60-7

SECTION 4. FIRST AID M	EASURES
Eyes	Immediately flush eyes with generous amounts of water for at least 15 minutes. Pullback the eyelid to ensure that all lime dust has been washed out. Seek medical attention immediately. Do not rub eyes.
Skin	Wash exposed area with large amounts of water. Seek medical attention immediately.
Ingestion	Do not induce vomiting. Seek medical attention immediately. Never give anything by mouth unless instructed to do so by medical personnel.
Inhalation	Move victim to fresh air. Seek medical attention if necessary. If breathing has stopped, give artificial respiration
Most Important Symptoms:	Irritation of skin, eyes, gastrointestinal tract, or respiratory tract.
Immediate Medical Attention /Special Treatment?	See first aid information above. Note to Physicians: Provide general supportive measures and treat symptomatically.

SECTION 5. FIRE FIGHTING MEASURES		
Suitable (and Unsuitable) Fire Extinguishing Media:	Use dry chemical fire extinguisher. Do not use water or halogenated compounds, except that large amounts of water may be used to deluge small quantities of this product.	
Specific Hazards Arising from the Product	Inhalation, skin, or eye contact can result in serious injury. This product is not combustible or flammable. However, this product may react violently with water, and can release heat sufficient to ignite combustible materials. This product is not considered to be an explosion hazard, although reaction with water or other incompatible materials may rupture containers. When this product is wet, it can be very slippery and can result in a slip hazard. Hazardous Combustion Products: None.	
Special Protective Equipment	Wear full fire-fighting turn-out gear (full Runker gear) and respiratory	

Special Protective Equipment
and Precautions for FireWear full fire-fighting turn-out gear (full Bunker gear), and respiratory
protection (SCBA) to prevent inhalation, skin, or eye contact.

Fighters



SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, Emergency Procedures	Avoid inhalation, eye, and skin contact. Avoid generating airborne dust. Wear appropriate protective clothing as described in section 8.
Methods and Materials for Containment and Clean Up	Utilize cleanup methods that minimize generating dust: vacuum. Avoid dry sweeping. Do not use water on large spills, as this product may react with water and release heat. Residue on surfaces may be removed with copious amount of water or vinegar.
SECTION 7. HANDLING	& STORAGE
Safe Handling	Avoid inhalation, skin, and eye contact. Avoid generating airborne dust. An eye wash station should be readily available when this product is handled.
Safe Storage	Keep in tightly closed containers. Protect containers from physical damage. Store in a cool, dry, and well-ventilated location. Do not store near incompatible materials (see Section 10 below). Keep away from moisture. Long-term storage in aluminum containers is not recommended, as calcium

oxide may corrode aluminum over long periods of time.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Other

ccupational Exposure Limits			
	OSHA PEL (mg/m³)	ACGIH TLV (mg/m³)	Ont. Reg. 833 TWAEV (mg/m³)
Calcium Carbonate	15 5 (respirable)	10	10
Calcium Oxide	5	2	2
Calcium Hydroxide	15 (total) 5 (respirable)	5	5
Calcium Magnesium Carbonate	-	-	-
Calcium Magnesium Oxide	-	-	-
Magnesium Carbonate	15 (total) 5 (respirable)	10	10
Magnesium Oxide	15	10	10
Silica - Crystalline Quartz	30 / (% silica +2) (total) 10 / (% silica +2) (respirable)	0.025 (respirable)	0.1
ngineering Controls	Use with adequate gene exposure below occupat		ventilation and to maintai ts.
ndividual Protection Measure	s (Personal Protective Equ	uipment):	
pecific Eye / Face Protection	Safety glasses with side shields. In windy conditions, or if work activity generates elevated airborne dust levels, dust proof or chemical goggles a recommended. Contact lenses should not be worn.		
pecific Skin Protection	When there is a risk of s prevent contact.	kin contact, wear a	opropriate clothing and glo
pecific Respiratory Protection	•		d particulate respirator, o concentrations, should be

accordance with applicable regulations and good industrial hygiene practices. An emergency eye wash fountain and shower are recommended.

Selection and use of the respiratory protective equipment must be in



SECTION 9. PHYSICAL & CHE	MICAL PROPERTIES
Appearance	White or grayish white material
Odor	Odorless
Odor Threshold	Not Applicable
pH at 25°C	12.45
Melting Point	2570°F (1410°C)
Boiling Point and Range	2849°F (1565°C)
Flash Point	Not Applicable
Evaporation Rate	Not Applicable
Flammability	Not Applicable
Upper/Lower Flammability or Explosive Limits	Not Applicable
Vapor Pressure/Density	Non-Volatile
Relative Density	1.04 -1.40
Solubility	0.100- 0.125 g/100g - but reacts with water to produce Ca(OH) $_{2}$ and heat Soluble in acids, glycerin, and sugar solutions
Partition Coefficient: N-Octanol/Water	Not Applicable
Auto-Ignition Temperature	Not Available
Decomposition Temperature	Not Available
Viscosity	Not Applicable

SECTION 10. STABILITY & REACTIVIT	SECTION 10. S	STABILITY 8	& REACTIVITY
-----------------------------------	---------------	-------------	--------------

Reactivity Chemical Stability	Reaction with water can release heat. Dangerous near organic materials may cause combustion. Reacts with carbon dioxide in air to form calcium carbonate. See incompatible materials list below. Stable under normal storage and handling conditions.	
Possibility of Hazardous Reactions	See reactivity section above.	
Conditions to Avoid	Vicinity of incompatible materials.	
Incompatibility	This product should not be mixed or stored with the following materials, due to the potential for strong reaction and release of heat: • water (unless in a controlled process) • acids • reactive fluoridated compounds • reactive brominated compounds • reactive powdered metals • reactive phosphorous compounds • aluminum powder • organic acid anhydrides • nitro-organic compounds • halogenated compounds	
Hazardous Decomposition Products	None	



SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure & Symptoms:

Eyes	Contact can cause severe irritation or burning of eyes, including permanent damage.
Skin	Contact can cause severe irritation or burning of skin, especially in the presence of moisture.
Ingestion	This product can cause severe irritation or burning of gastrointestinal tract if swallowed.
Inhalation	This product can cause severe irritation of the respiratory system.
Chronic Health Effects	This product contains trace amounts of crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica can cause silicosis, as serious lung disease.
Respiratory or Skin Sensitization	This material is not known to cause sensitization
Germ Cell Mutagenicity	No data available.
Carcinogenicity	This product is not listed as carcinogenic by OSHA, IARC, NTP, ACGIH, or the EU Directives. This product may contain trace amounts of crystalline silica quartz which is listed by IARC as "Carcinogenic to Humans" (Group 1) and "Known to be a Human Carcinogen" by NTP (National Toxicology Program).
Reproductive Toxicity	No Data Available
Numerical Measures of Toxicity	Crystalline Silica: Oral (rat) LD50 > 22,500 mg/kg Calcium hydroxide: Oral (rad) LD50: 7340 mg/kg Calcium oxide: Oral (rat) LD50: 3059 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Because of the elevated pH of this product, it might be expected to produce some ecotoxicity upon exposure to certain aquatic organisms and aquatic systems in high concentrations. This material shows no bioaccumulation effect or food chain concentration toxicity.

SECTION 13. DISPOSAL CONSIDERATIONS

Because of the elevated pH of this product, it might be expected to produce some ecotoxicity upon exposure to certain aquatic organisms and aquatic systems in high concentrations. This material shows no bioaccumulation effect or food chain concentration toxicity.

SECTION 14. TRANSPORT INFORMATION		
UN Number	UN1910	
UN Proper Shipping Name	Calcium Oxide	
Transport Hazard Class(es)	When transported by air only: Hazard Class 8-Corrosive	
Packing Group	When transported by air only: Packing Group III	
Environmental Hazards	This material is alkaline and if released into water or moist soil will cause an increase in pH	



Transport in Bulk (According to Annex II of MARPOL 73/79 and the IBC Code:

Special Precautions Which a User Needs to be Aware of: When being transported by air, calcium oxide is classified in the Department of Transportation (DOT) regulations as a hazardous material. (49 CFR 172.101). For aircraft transport only, Calcium Oxide is classified as Hazard Class 8-Corrosive, UN1910, Packing Group III. For passenger aircraft, the maximum net quantity allowed per container is 25 kg. For cargo aircraft, the maximum net quantity allowed per container is 100 kg. For quantities greater than 25 kg up to and including 100 kg, the container shall be labeled with CARGO AIRCRAFT ONLY. Because express carriers (i.e., Federal Express, Airborne Express, and United Parcel Service) ship by air, calcium oxide presented to these carriers for shipment must be packaged, marked, and labeled in accordance with IATA requirements, and must be accompanied by the appropriate shipping documentation. Only personnel trained and certified under applicable DOT Hazardous Materials Regulations (contained in Title 49 of the Code of Federal Regulations) may prepare any calcium oxide product for air transport. Calcium oxide is not classified as a hazardous material by DOT when transported by means other than by air.

SECTION 15. REGULATORY INFORMATION	
CERCLA Hazardous Substances	Not Listed
SARA Toxic Chemical (40 CFR 372.65)	Not listed
SARA Section 302 Extremely Hazardous Substances (40 CFR 355)	Not listed
SARA 311/312	Not listed
SARA Section 313 Toxic Chemicals reporting requirements	None
Threshold planning quantity (TPQ)	Not listed
RCRA Hazardous Waste Classification (40 CFR 261)	Not Classified
EPA Toxic Substances Control Act (TSCA) Status	All of the components of this product are listed on the TSCA
California Proposition 65	Airborne crystalline silica particulates of respirable size are known to the State of California to cause cancer.
NFPA Ratings	Health: 3 Fire: 0 Reactivity: 2 ₩
HMIS Ratings	Health: 3 Fire: 0 Reactivity: 2 Personal protection: E
OSHA Specifically Regulated Substance (29 CFR 1910)	Not listed
OSHA Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A)	Listed
MSHA	Not listed
Canada DSL	Listed
Canadian WHMIS Classification	D2A, Materials Causing other toxic effects. E, Corrosive Material
Canada CPR	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation of a Canada and this SDS contains all the required information.



SECTION 16. OTHER INFORMATION

List of GH Statemen	
List of GH Precautic Statemen	nary P202: Do not handle until all safety precautions have been read and understood.
Abbreviat	ions
CERCLA	Comprehensive Environmental Response, RCRA Resource Conservation and Recovery Act Compensation and Liability Act
SARA	Superfund Amendments and IARC International Agency for Research on Cancer Reauthorization Act
NTP	National Toxicology Program

The information contained herein is believed to be accurate and reliable as of the date hereof. However, Mintek Resources makes no representation, warranty or guarantee as to results or as to the information's accuracy, reliability, or completeness. Mintek Resources has no liability for any loss or damage that may result from use of the information. Each user is responsible to review this information, satisfy itself as to the information's suitability and completeness, and circulate the information to its employees, customers and other appropriate third parties.